



COMPOSITION 81% polyester, 19% acrylic

WIDTH 137cm

WEIGHT 420gsm

PATTERN REPEAT nil

ROLL SIZE 50m approx.

CARE CODE CTA 1

ABRASION

Wyzenbeek ASTM 4157 Martindale AS2001.2.25 >100,000 double rubs

>40,000

CTA RATING

hc

HEAVY DUTY COMMERCIAL USE

SEAM SLIPPAGE AS2001.2.22 Warp 3.3mm Weft 5.8mm Note: All seams must be overlocked or secured to prevent the premature failure of the seam due to fraying

PILLING 5

Martindale IWS196

LIGHTFASTNESS ISO 105/B02 >6

FIRE RATINGS

AS/NZS 1530.3 Ignitability 11
Spread of Flame 0
Heat Evolved 3
Smoke Developed 5

AS/NZS 3837 (AS 5637.1) BCA Group 1

Av. Specific Extinction Area 144.5m2/kg

ISO 5660.1 NZBC Group 1S

Av. Specific Extinction Area 125.8m2/kg

APPLICATION upholstery, screens, wall panels

ORIGIN Made in Australia

PLEASE NOTE Results from performance tests are

guidelines only

ENVIRONMENT

Manufacturer has reduced water + energy use and recycles waste.

GREEN STAR

AGILE can be used on white furniture certified to Ecospecifier, AFRDI, ECNZ and GECA

The Green Star Rating Tool states "Where at least 90% of an item's mass is certified to a GBCA recognised standard, the item can be entered as a certified product at Level A, B or C." Therefore any fabric can be used as fabrics are almost always under 10% by weight of a furniture item

WELL

AGILE can contribute to the following WELL criteria:

 Toxic Material Reduction: AGILE is free of PFCs, flame retardants, phthalates and urea formaldehyde

