

# TATAMI


An elegant and contemporary screen texture that echoes beauty and simplicity.



INSTYLE





COMPOSITION	50% polypropylene, 35% acrylic, 15% polyester	
WIDTH	188cm	
WEIGHT	280gsm	
PATTERN REPEAT	nil	
ROLL SIZE	50m approx.	
CARE CODE	Screens	
CTA RATING		COMMERCIAL
		SCREEN FABRICS
LIGHTFASTNESS ISO 105-B02	6/7	
FIRE RATINGS AS/NZS 1530.3	Ignitability	13
	Spread of Flame	0
	Heat Evolved	3
	Smoke Developed	3
AS/NZS 3837	BCA Group 2 Av. Specific Extinction Area 87 m2/kg	
APPLICATION	screens, wall panels	

#### ENVIRONMENT

- 50% low embodied-energy material: polypropylene has a lower embodied-energy compared to polyester and nylon.
- Environmentally Improved Production Process: reduced energy consumption, reuse and recycling of waste

#### GREEN STAR

- TATAMI can be used on white vertical surfaces certified to Ecospecifier, AFRDI, ECNZ and GECA.
- The Green Star Rating Tool states "Where at least 90% of an item's total mass is certified to a GBCA recognised standard, the item can be entered as a certified product at Level A, B or C". Any fabric can be used as fabrics are almost always under 10% by weight of a furniture item.