

Ecooustic® Dangaay

—
Big rain coming, then the dry, an acoustic panel print by
Wiradjuri artist Amanda Hinkelman + Instyle Design Studio





Dangaay White on Natural
White core



Dangaay Ochre on Natural
White core



Dangaay Biscuit on Oyster
White core



Dangaay White on Dove
White core



Dangaay Black on Taupe
Black core



Dangaay Blue on Indigo
Black core

Patterns shown are not to scale
Product may vary in colour due to the nature of the media
Please refer to website for current colour range



COMPOSITION	100% PET (up to 65% recycled PET) + water-based ink
THICKNESS	8mm (stock item) 13.5mm*, 25mm*, 50mm* + 12mm Screen*
PRINT DIMENSIONS	Panel: 1200 x 2700mm approx. Screen: 2400 x 1200mm approx.
PATTERN REPEAT	H: 1200mm V: 2700mm The pattern is railroaded for Ecoustic® Screen
FIRE RATINGS	AS/NZS 1530.3: 8mm, 13.5mm, 12mm Screen AS/ISO 9705 Group 1 (AS 5637.1) GB 8624-2012 Grade B1 (8mm Panel)
ACOUSTIC	NRC 0.3 - 1.0 / αw 0.34 - 1.0
APPLICATION	Screen, wall + ceiling panel
ORIGIN	Made in Australia
EDGING	Natural anodised aluminium edging are available for all Ecoustic® Panel thicknesses + T Trims in natural or black anodised
PLEASE NOTE	Results from performance tests are guidelines only. Onsite trimming to square each individual panel is essential. This is a screen printed product. Variation in thickness, fibre mix and colour as well as flecks + other slight surface blemishes are an inherent feature of this product and are unavoidable. Variation from batch to batch may occur. Interior products must be protected from direct heat + sunlight.
WARRANTY	5 year conditional warranty against manufacturing defects. This applies to internal installation only, outdoor use will void any warranty.

BENEFITS

Improved Pinability: Ecoustic® Panel + Screen features an improved pinability compared to similar panel products.

Lightweight, Easy to Handle + Install: Ecoustic® is an intelligent alternative to traditional panels composed of multiple materials such as particle board, fabric, foam and adhesive.

Designed for the Environment



Giving Back: % of sales are donated to the Nature Conservancy.

Building Rating Systems: Ecoustic® Dangaay will contribute the following points for Green Star, LEED + WELL building standards.

Criteria	Green Star	LEED	WELL
Recycled Content	√	√	NA
Low VOC	√	√	√
Recycling Program	√	√	NA
EPD	√	√	NA
Declare Label	NA	√	√
Greentag Level A Certification	√	√	√
Toxic Material Reduction	NA	NA	√
Sound Reducing Surfaces 25mm + 50mm	NA	NA	√

HOW TO SPECIFY

DESIGN	Ecoustic® Dangaay
PRODUCT	Panel (Single Side) or 12mm Screen* (Double Side)
PANEL THICKNESS	8mm, 13.5mm*, 25mm* or 50mm* *minimums apply
COLOUR	Select from Dangaay colours
EDGING	Optional extra - order separately

The sound absorption has been tested in accordance with AS/ISO 354. For complete test reports please contact your local distributor.

