

# Ecooustic® Opus



An acoustic panel with a large-scale organic design



INSTYLE



**COMPOSITION** 100% PET (up to 65% recycled PET)

**THICKNESS** 8mm\*, 13.5mm\*, 25mm\*, 50mm\* + 12mm Screen\*

**PRINT DIMENSIONS** Panel: 1200 x 2700mm approx.  
Screen: 2400 x 1200mm approx.

**PATTERN REPEAT** H: 1200mm V: 2700mm  
Opus is railroaded for Ecoustic® Screen

**FIRE RATINGS** AS/NZS 1530.3  
AS/ISO 9705 Group 1  
GB 8624-2012 Grade B1 (8mm Panel)  
Refer to Ecoustic® Panel + Screen specification

**ACOUSTIC AS/ISO 354** NRC 0.3 - 1.0 /  $\alpha_w$  0.34 - 1.0  
Depending on panel thickness, refer to Ecoustic® Panel + Screen information

**APPLICATION** Screen, wall + ceiling panel

**ORIGIN** Made in Australia

**EDGING** Natural anodised aluminium edging are available for all Ecoustic® Panel thicknesses + T Trims in natural anodised or black powdercoat

**PLEASE NOTE** Results from performance tests are guidelines only  
Onsite trimming to square each individual panel is essential  
This is a hand printed product. Variation in thickness, fibre mix and colour as well as flecks + other slight surface blemishes are an inherent feature of this product and are unavoidable. Variation from batch to batch may occur  
Interior products must be protected from direct heat + sunlight

**WARRANTY** 5 year conditional warranty against manufacturing defects. This applies to internal installation only, outdoor use will void any warranty

INSTYLE.COM.AU

## BENEFITS

**Improved Pinability:** Ecoustic® Panel + Screen features an improved pinability compared to similar panel products.

**Lightweight, Easy to Handle + Install:** Ecoustic® is an intelligent alternative to traditional panels composed of multiple materials such as particle board, fabric, foam and adhesive.

## Designed for the Environment



**Building Rating Systems:** Ecoustic® Opus will contribute the following points for Green Star, LEED + WELL building standards.

Criteria	Green Star	LEED	WELL
Recycled Content	✓	✓	NA
Low VOC	✓	✓	✓
Recycling Program	✓	✓	NA
EPD	✓	✓	NA
Declare Label	NA	✓	NA
Greentag Level A Certification	✓	✓	✓
Toxic Material Reduction	NA	NA	✓
Sound Reducing Surfaces 25mm + 50mm	NA	NA	✓

## HOW TO SPECIFY

<b>DESIGN</b>	Ecoustic® Opus
<b>PRODUCT</b>	Panel (Single Side) or 12mm Screen* (Double Side)
<b>PANEL THICKNESS</b>	8mm*, 13.5mm*, 25mm* or 50mm* *minimums apply
<b>COLOUR</b>	Select from Opus colours
<b>EDGING</b>	Optional extra - order separately

The sound absorption has been tested in accordance with AS/ISO 354. For complete test reports please contact your local distributor.



