

Ecoustic® Tri

—
A striking acoustic panel print designed
by Michael Young



INSTYLE



COMPOSITION 100% PET (up to 65% recycled PET)

THICKNESS 8mm*, 13.5mm*, 25mm*, 50mm* + 12mm Screen*

PRINT DIMENSIONS Panel: 1200 x 2700mm approx.
Screen: 2400 x 1200mm approx.

PATTERN REPEAT H: 450mm V: 430mm
TRI is railroaded for Ecoustic® Screen

FIRE RATINGS AS/NZS 1530.3
AS/ISO 9705 Group 1
GB 8624-2012 Grade B1 (8mm Panel)
Refer to Ecoustic® Panel + Screen specification

ACOUSTIC AS/ISO 354 NRC 0.3 - 1.0 / α_w 0.34 - 1.0
Depending on panel thickness, refer to Ecoustic® Panel + Screen information

APPLICATION Screen, wall + ceiling panel

ORIGIN Made in Australia

EDGING Natural anodised aluminium edging are available for all Ecoustic® Panel thicknesses + T Trims in natural anodised or black powdercoat

PLEASE NOTE Results from performance tests are guidelines only
Onsite trimming to square each individual panel is essential
This is a hand printed product.
Variation in thickness, fibre mix and colour as well as flecks + other slight surface blemishes are an inherent feature of this product and are unavoidable. Variation from batch to batch may occur
Interior products must be protected from direct heat + sunlight

WARRANTY 5 year conditional warranty against manufacturing defects. This applies to internal installation only, outdoor use will void any warranty

INSTYLE.COM.AU

BENEFITS

Improved Pinability: Ecoustic® features an improved pinability compared to similar panel products.

Lightweight, Easy to Handle + Install: Ecoustic® is an intelligent alternative to traditional panels composed of multiple materials such as particle board, fabric, foam and adhesive.

Designed for the Environment



Building Rating Systems: Ecoustic® Tri will contribute the following points for Green Star, LEED + WELL building standards.

Criteria	Green Star	LEED	WELL
Recycled Content	✓	✓	NA
Low VOC	✓	✓	✓
Recycling Program	✓	✓	NA
EPD	✓	✓	NA
Declare Label	NA	✓	NA
Greentag Level A Certification	✓	✓	✓
Toxic Material Reduction	NA	NA	✓
Sound Reducing Surfaces 25mm + 50mm	NA	NA	✓

HOW TO SPECIFY

DESIGN	Ecoustic® Tri
PRODUCT	Panel (Single Side) or 12mm Screen* (Double Side)
PANEL THICKNESS	8mm*, 13.5mm*, 25mm* or 50mm* *minimums apply
COLOUR	Select from Tri colours
EDGING	Optional extra - order separately

The sound absorption has been tested in accordance with AS/ISO 354. For complete test reports please contact your local distributor.

