

COMPOSITION 100% phthalate-free vinyl, Osnaburg

backing

WIDTH 132cm (trimmed) approx

WEIGHT 453gsm approx

PATTERN REPEAT non-match

ROLL SIZE 45.8m approx. Note: minimum order

quantity is 0.9m and 0.9m multiples

PERFORMANCE Type II Wallcovering

Easy to clean Bleach cleanable

Additional Fire Tests AS/NZS 3837 (AS 5637.1) Group 1

ASTM E-84 (adhered) Tunnel Test

Class A

ENVIRONMENT

- Low VOC certified
- All wallcoverings meet the stringent criteria of the Collaborative for High Performance Schools (CHPS Section 01350)
- Free of formaldehyde, phthalates + heavy metals for healthy indoor environment

WARRANTY

For a period of 3 years from date of invoice this wallcovering
is guaranteed to be first quality and free of manufacturing
defects. This warranty applies only to professionally applied
installations according to the recommended installation
instructions, and proper care and maintenance using
appropriate cleaning agents as outlined in the care and
maintenance instructions.

MOULD + MILDEW

 This product is intended for use in properly built and maintained buildings that are not subject to moisture accumulation in a wall or wall cavity at any time. Application must follow current installation guidelines.

PRODUCT INSTALLATION

Detailed installation instructions for Concertex wallcoverings are supplied with each shipment and should be referred to before cutting or installing this wallcovering.

CARE + MAINTENANCE

- General maintenance can be achieved with periodic dusting or vacuuming with a soft brush attachment.
- Remove ordinary dirt and smudges with a mild soap and warm water solution.
- Avoid all solvent based cleaners.
- Always test the solution on an inconspicuous portion of the wallcovering before proceeding, checking that there is no adverse effect on finish, colour or gloss.
- Care should be taken on dark colours due to the possibility of causing 'light marks'. Always use a blotting action rather than rubbing to avoid abrasion.
- Rinse lightly with clean water and sponge.
- Deeply embossed wallcoverings need extra attention in case suds or loosened dirt lodge in depressed surfaces.
- Dry with a soft lint free cloth or towel.

COLOURWAYS





Arctic

Field

HOW TO SPECIFY	
PRODUCT	Dominion
COLOURWAY	Select from Dominion colourways





